



Item No. 62444 Delock Audio Converter Digital > Analogue

Description

The Delock audio converter changes your digital signal into an analogue stereo signal. At the input port of the device you can connect e. g. your digital DVD or Blu-ray player to input the digital signal whether optical via Toslink or via coaxial connection. At the output port the analogue signal will be transmitted through the RCA connection to the analogue device.



Specification

Connector:

Input:	1 x Toslink S/PDIF
	1 x Coaxial S/PDIF

- Output: 2 x RCA red / white
- 1 x DC power supply connector 5 V
- Electromagnetic-noise-free transmission
- · Supports different audio rates, e. g. 32, 44.1, 48 and 96 KHz
- Dimension (LxWxH): ca. 63 x 41 x 21 mm

Power supply specification

Wall power supply

- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.5 A
- Output: 5 V / 2 A
- · Ground outside, plus inside
- Dimensions: inside: ø ca. 2.1 mm outside: ø ca. 5.5 mm length: ca. 9 mm

System requirements


- Digital audio signal
- Connection cables

Package content

- Converter digital > analogue
- Power supply
- User manual

Images





Additional Information

EAN: 4043619624447

Country of origin: China

Package: White Box





