



Delock Cable Displayport 1.2 male > Displayport male 4K 2 m

Description

This cable enables you to connect Displayport devices e.g. a monitor to your PC. The Displayport is standardized universal connecting standard by VESA for the transfer of video and audiosignal. It can be applied for monitors, TV to computer, DVD-player and similar devices.



2 m

ltem no. 82585

EAN: 4043619825851

Country of origin: China

Package: Poly bag

Specification

- Connector: Displayport 20 pin male > Displayport 20 pin male
- Displayport 1.2 specification
- 20 pin is connected (supports 3.3 V)
- Cable gauge: 30 AWG data line 28 AWG power line
- Cable diameter: ca. 6 mm
- Twisted-pair cabling
- Copper conductor
- · Gold-plated connector
- Triple shielded cable
- Transfer of audio and video signals
- Data transfer rate up to 21.6 Gb/s
- Resolution up to 3840 x 2160 @ 60 Hz (depending on the system and the connected hardware)
- Colour: black
- Length incl. connector: ca. 2 m

System requirements

· A free Displayport interface

Package content

Displayport cable

Images



Here Data sheet



General	
Specification:	standard
	Displayport 1.2
Interface	
connector 1:	standard
	1 x Displayport 20 pin male
connector 2:	standard
	1 x Displayport 20 pin male
Technical characteristics	
Data transfer rate:	standard
	21,6 Gb/s
Maximum screen resolution:	standard
	3840 x 2160 @ 60 Hz
Physical characteristics	
Housing material:	standard
	PVC
Cable diameter:	standard
	6 mm
Connector finishing:	standard
	gold-plated
Pin finishing:	standard
	gold-plated
Conductor material:	standard
	copper
Conductor gauge:	standard
	30 AWG data line
	28 AWG power line
Shielding:	standard
	triple
Length:	standard
	2 m
Colour:	standard
	black