

# Delock Active Optical USB-C<sup>™</sup> Video + Data + PD Cable 10 m

# Description

This USB cable by Delock enables the connection between a device with a USB Type- $C^{TM}$  connector and a PC or a laptop equipped with a free USB Type- $C^{TM}$  port.

#### Active Optical Cable

This active optical cable uses optical fiber to transmit high-speed signals. Compared to traditional copper cable, it is softer, thinner, lighter, and can transmit signals over longer distances without loss.

#### **DisplayPort 1.4 with 2 lanes**

The cable is suitable for connecting a USB-C<sup>™</sup> monitor with resolution up to 4K Ultra HD (3840 x 2160 @ 144 Hz) to a computer with USB-C<sup>™</sup> interface and DisplayPort Alternate Mode support.

#### USB 3.2 Gen 2 with 10 Gbps

The active optical cable enables data transfer rates of up to 10 Gbps when connecting USB 3.2 Gen 2 compatible devices. Of course, USB 2.0 devices can also be connected.

#### USB Power Delivery support up to 60 watt

Supporting the USB Power Delivery standard, connected devices can be powered up to 60 W (20 V / 3 A).

#### Note

This cable is only compatible with DisplayPort (DP alt mode) devices and it will not work with Thunderbolt<sup>TM</sup> devices.

# Specification

- Connectors:
  - 2 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-C™ male
- Active optical cable: fiber / copper hybrid cable
- Supports 2 lanes DisplayPort 1.4



#### Item no. 84150

EAN: 4043619841509 Country of origin: China Package: Box

## **DATASHEET**



- Supports Display Stream Compression 1.2 (DSC)
- Supports DP Alt Mode
- Transmission of audio and video signals
- Maximum resolution (depending on the system and the connected hardware): DisplayPort 1.4 with DSC: up to 3840 x 2160 @ 144 Hz
  DisplayPort 1.4 without DSC: up to 3840 x 2160 @ 60 Hz
  DisplayPort 1.2 without DSC: up to 3840 x 2160 @ 30 Hz
- Supports HDR (High Dynamic Range)
- Supports HDCP 1.4 and 2.2
- Fixed signal direction for video (Source / Display)
- Non-directional for data
- Data transfer rate up to SuperSpeed USB 10 Gbps
- Downwards compatible to USB 2.0
- Output current: up to 3 A
- Cable diameter: ca. 6.5 mm
- Colour: black
- Length incl. connectors: ca. 10 m

# System requirements

- PC or laptop with a free USB Type-C™ port and DisplayPort alternate mode
- Monitor with a free USB Type-C<sup>™</sup> (DP Alt Mode) interface

# Package content

• SuperSpeed USB 10 Gbps cable

#### Images





### General

| Specification: | USB Type-C™                    |  |
|----------------|--------------------------------|--|
| Interface      |                                |  |
| Connector 1:   | 1 x USB 3.2 Gen 2 Type-C™ male |  |
| Connector 2:   | 1 x USB 3.2 Gen 2 Type-C™ male |  |

# **Technical characteristics**

| Data transfer rate:        | USB 3.2 Gen 2 bis zu 10 Gb/s |
|----------------------------|------------------------------|
| Operating temperature:     | -10 °C ~ 50 °C               |
| Maximum screen resolution: | 3840 x 2160 @ 144Hz          |
| Maximum current:           | 3 A                          |

# **Physical characteristics**

| Cable colour:                 | black  |
|-------------------------------|--------|
| Cable diameter:               | 6.5 mm |
| Cable length incl. connector: | 10 m   |
| Smallest bending radius:      | 60 mm  |