



GEL-1061 Έκδοση υλικού (h/w): 1

10-Port L2 Managed Gigabit Switch, 2 x SFP

The GEL-1061 is a L2 managed switches designed for the SMB market. The switches can be deployed indifferent target network topologies, from small to large. As well as IPv4 and IPv6 features. The GEL-1061 includes the best green-saving technologies (IEEE 802.3az and Green-Ethernet). Using the Energy Efficient Ethernet standard, the switch automatically decreases power usage when network traffic is low.

Βασικά χαρακτηριστικά

- Spanning Tree Protocol (STP) (IEEE 802.1d/w/s) και κατοπτρισμός θυρών
- LACP (IEEE 802.3ad) για αυτόματες συγκεντρώσεις θυρών
- Έλεγχος ταυτότητας (IEEE 802.1X) βάσει θύρας με Λίστα Ελέγχου Πρόσβασης (Access Control List - ACL) που αποτελείται από έως και 512 καταχωρήσεις για απλή ασφάλεια δικτύου
- IP Multicast Filtering through IGMP Snooping V1 / V2 / V3
- Supports port-based VLAN, IEEE 802.1Q VLAN Tagging
- Διαχείριση και ανάπτυξη σε λειτουργία δικτύου IPv6
- IEEE 802.1p QoS με 8 ουρές προτεραιότητας

Προδιαγραφές

System Specifications

Standards & Protocols:

IEEE 802.3 10-BASE-T, Ethernet
 IEEE 802.3u 100-BASE-TX, Fast Ethernet
 IEEE 802.3ab 1000BASE-T, Gigabit Ethernet
 IEEE 802.3z 1000BASE-X, Gigabit Ethernet
 IEEE 802.1p Quality of Service (QoS)
 IEEE 802.1Q Virtual LANs (VLANs)
 IEEE 802.1D MAC Bridges
 IEEE 802.1d Standard Spanning Tree Protocol
 IEEE 802.1s Multiple Spanning Tree (MSTP)
 IEEE 802.1w Rapid Spanning Tree Protocol (RSTP)
 IEEE 802.3x Flow Control
 IEEE 802.3ad Link Aggregation Control Protocol (LACP)
 IEEE 802.3az Energy-Efficient Ethernet
 Link Layer Discovery Protocol (LLDP)
 Universal Plug and Play (UPnP)

Memory:

32MB

**Buffer Memory:**

4.1Mbits

Connectors and Cabling:

8x RJ-45 10/100/1000BASE-T ports

2 x 100/1000Base-X SFP Slots

Button/Knob:

Reset / Factory Default Button

Indicator:

Power; Link/Active

Transmission Method:

Store-and-Forward

Power Input:

100-240V AC, 50-60 Hz, Internal Power Supply

Power Consumption:

< 8W

Features

General:

Quality of Service (QoS):

8 hardware Priority Queues per port

Traffic classification based on IEEE 802.1p CoS

IPv4/IPv6 precedence/ type of service (ToS) / DSCP based

Rate Limiting - Ingress policer egress shaping and rate control

Spanning Tree:

Bridge Protocol Data Units (BPDU)

IEEE 802.1D MAC Bridges

IEEE 802.1d Spanning Tree Protocol (STP)

IEEE 802.1w Rapid Spanning Tree Protocol (RSTP)

IEEE 802.1s Multiple Spanning Tree Protocol (MSTP)

Virtual Local Area Network (VLAN):

802.1Q tag-based VLAN - up to 4K VLANs and 4K VLAN IDs

Port-based VLAN

MAC-based VLAN

DHCP: DHCP Client; DHCP Relay (Layer 2)

IPv6:

IPv6 Ping / Trace /Telnet / Syslog / TFTP

IGMP:

IGMP v1/v2/v3 snooping; IGMP Queried; IGMP Filtering /Throtting

Port Mirroring:

One to One /One to Many

IEEE 802.3ad LACP Trunk

Security:

DDOS Protection

CPU Guard

Port Isolation

Port Mirror /Remote Mirror

Broadcast / Multicast / Unknown Storm Control

802.1X

ACL

Port Security

MAC Filter / MAC Authentication

AAA

IP Source Guard

SSH

Management:

System Password protection
NTP/SNTP
Dual Image /Configuration
Firmware upgrade /download (HTTP/TFTP/FTP)
RMON/ SNMP
Management Access (Console / SNMP/ Web / Telnet)
Memory Flash Log
Event /Error Log
DHCP v4/v6 Snooping
DHCP Snooping Option82

Ease of Use:

Dashboard

Performance**Backplane (Gbps):**

20Gbps

MAC Address Table:

8K

Data Transfer Rate:

10/100/1000Mbps

Packet Forwarding Rate:

14.9 Mpps

Jumbo Frame (K):

10K

Environment**Power Saving:**

IEEE 802.3az Energy Efficient Ethernet:

- Automatically turns power off on RJ-45 port when detecting link down or Idle of client
- Cable length detection: Adjusts the signal strength based on the cable length
- Reduces the power consumption for cables shorter

Acoustic Noise:

0 dB (A)

Heat Dissipation:

27.297 (Btu/H)

Temperature (°C):

0-50 C

Humidity (Non-condensing):

10-90%

Deployment:

desktop

Physical Specifications**Dimensions (W x D x H mm):**

19.6x11.7x3.6mm

Weight (g):

Gross: 3007g

Net: 817g



Reliability

MTBF:

25 degreeC: 1284936 hrs

45 degreeC: 55390 hrs

Approval and Compliance

EMI/EMS:

CE classA, FCC, UL, VCCI, BSMI

Order Information

GEL-1061

Περιεχόμενα συσκευασίας

GEL-1061

Power Cord

19" Rack Mount Kit

Quick Installation Guide

Resource CD (User Manual)

Console Cable