



4GE PoE + 1GE Switch

H/W Version: 2

Product Overview

The LevelOne GEP-0520 provides 5 x 10/100/1000Mbps ports with IEEE 802.3af PoE supported. This switch is IEEE 802.3af compliant, and provides power and data over a single Ethernet cable to any PoE device, with total power budget of 61.6W, up to 15.4W per port. Together with Energy Efficient Ethernet (IEEE 802.3az) standard compliant, it substantially lower power consumption during periods of low-link utilization.



GEP-0520

Moreover, supports Gigabit Ethernet connectivity with 9K jumbo frames for network performing enhancement. Ideal for small businesses that prefer an inexpensive solution for PoE deploying infrastructure.



- 1. LED Indicators
- 2. 10/100/1000Mbps RJ-45 Uplink Port
- 3. External power socket
- 4.10/100/1000Mbps RJ-45 PoE Ports

Key Features

- IEEE 802.3af PoE compliant to simplify deployment and installation
- Minimize carbon footprint with advanced energy efficient technology (IEEE 802.3az)
- 9K jumbo frames to increase data transfer rates
- Auto-detection and protection of non-standard PoE devices
- IEEE 802.3x flow control protects against lost packets for reliable data transmission
- Total PoE power budget: 61.6W, up to 15.4W per port

Works Well With



POC-6000 8-Bay High Power PoE Chassis for FSW-0503(-Z) / FSW-0513(-Z) / GEP-0520(-Z)



WAP-6012 300Mbps Wireless Gigabit PoE Access Point

Technical Specifications

Standards

IEEE 802.3: 10 BASE-T IEEE 802.3u: 100 BASE-TX IEEE 802.3ab: 1000 BASE-T IEEE 802.3af: Power over Ethernet IEEE 802.3az: Energy Efficient Ethernet

Features

MAC Address: 2K Buffer Memory: 128KB Transmission Method: Store-and-Forward Backplane: 10Gbps Jumbo Frame: 9K

Filtering/Forwarding Rates

1000Mbps port-1488,000pps 100Mbps port-148,000pps 10Mbps port-14,880pps

Transmission Media

10Base T Cat. 3, 4, 5 UTP/STP 100Base TX Cat. 5 UTP/STP 1000Base TX Cat. 5e/6/7 UTP/STP

Network Interface

4 x 10/100/1000Mbps RJ-45 PoE Ports 1 x 10/100/1000Mbps RJ-45 Uplink Port

	PoE Spec
	PoE Standard: IEEE 802.3af Power over Ethernet
	PD classification identity
	PoE over current protection
	PoE circuit sorting protection
	PoE Power Output: Per Port 48V DC, Max. 15.4 watts (802.3af)
_	PoE Power Budget 61.6W
	Power Pin Assignment: 1/2(+), 3/6(-)
	Power Consumption
	65W
	LED Indicators
_	Power, Uplink, LAN 1~4 port, PoE 1~4 port
	Power Input
	100-240VAC / 50-60Hz External Power Adapter
	Dimensions (L x W x H)
_	120 x 90 x 28mm
	Weight
	0.8kg
	Temperature
_	Operating: 0~45 Degree °C
	Storage: -40~70 Degree °C
	Humidity
_	Operating: 10~90% (Non-condensing)
	Storage: 10~90% (Non-condensing)
	Certifications
	FCC, CE

Product Diagram

PoE



Order Information	GEP-0520: 4GE PoE + 1GE Switch
Package Contents	GEP-0520, Power Adapter, Quick Installation Guide

Optional Accessories



POC-6000 8-Bay High Power PoE Chassis for FSW-0503(-Z) / FSW-0513(-Z) / GEP-0520(-Z)

All mentioned brand names are registered trademarks and property of their owners. Technical specifications are subject to change without notice.

 $\ensuremath{\mathbb{C}}$ Copyright Digital Data Communications GmbH. All Rights Reserved.