



POI-3014 Version: 1

Gigabit PoE Injector, 30W

"The LevelOne POI-3014 is a Power over Ethernet (PoE) injector that not only delivers a cost-effective solution for power distribution, but also provides a seamless way of deploying Powered Devices (PDs) on existing LAN infrastructure.

With the use of power injectors, DC power of up to 30W and the data that comes from a non-PoE switch are merged together and then transmitted to a PD such as a PoE network camera, through the Ethernet cabling. This allows you to extend the use of your existing hardware investment without needing to buy extra PoE switches.

Furthermore, non-PoE devices like wireless access points can also be powered up remotely by adding additional PoE splitters, since power and data are further split into two cables. These devices can therefore be installed in hard-to-reach areas like ceilings where there are no outlets or electrical wiring nearby."

Key Features

- Remove the need for a bulky power adapter and power line
- Delivers power and data to equipment via a single Ethernet cable
- Remote power feeding up to 100m
- Unique interlocking feature for easy installation
- Surge protected to enhance safety
- Simple Plug and Play installation
- Compact, lightweight design
- Total PoE power budget: 30W, up to 30W per port

Specifications

System Specifications

Standards & Protocols:

IEEE 802.3 10Base-T, Ethernet
IEEE 802.3u 100Base-TX, Fast Ethernet
IEEE 802.3ab 1000Base-T, Gigabit Ethernet

Port:

1 x 10/100/1000Base-T RJ-45 Input Port
1 x 10/100/1000Base-T RJ-45 PoE Output Port

Indicator:

Power, PoE

**Pin Assignment and Polarity:**

4/5 (+), 7/8 (-)

Power Input:

PoE Power Output: DC 52V / 30W

Unit Output Voltage: DC 52V / 0.6A

Power Requirement: 100-240V AC, 50/60Hz, 0.8A

Power Consumption: 30W (Max.)

Operating Temperature (°C):

0°C ~ 45°C

Operating Humidity (Non-condensing):

5 ~ 95%

Storage Temperature (°C):

0°C ~ 70°C

Storage Humidity (Non-condensing):

5% ~ 95%

Mount:

Wall mount

Physical Specifications

Dimensions (W x D x H mm):

64.39 x 43.4 x 145.7 mm

Weight (g):

350g

Reliability

MTBF:

87.1K (hours)

Approval and Compliance

EMI/EMS:

FCC Part 15, CE, RoHS

Order Information

POI-3014

Package Contents

POI-3014

Quick Installation Guide