

USB-0502 Version: 1

Gigabit USB Network Adapter with USB Hub

Fast and easy connection with USB

The LevelOne Gigabit USB Network Adapter with 3-Port USB Hub allows easy connection to the internet through the built-in USB port on your laptop or gaming console. Now you no longer need to have an Ethernet connection in order to surf the web. This is an ideal solution for MacBook Air (100% Mac compatible) or other computers that may have wireless built-in but don't come with an Ethernet port. Sometimes you need to physically connect to a network cable to help transfer files or access secure information. The USB-0502 easily does the job, all through your USB port. The USB-0502 also provides a USB hub with 3 extra ports, so you can connect external USB peripherals such as an MP3 player, digital camera, printer or pen drive. The USB-0502 establishes a direct point-to-point contact between the hub and the adapter that's plugged into your PC.

Reliable, efficient and standards compliant

The USB-0502 is USB 2.0 and 3.0 compliant. It also follows Ethernet standards 802.3, 802.3u and 802.3ab as set by the IEEE, allowing you to take advantage of Gigabit Ethernet speeds of up to 1000Mbps. This provides a strong backbone for any high-speed broadband connection to the internet as well as fast speeds for Local Area Network file transfers.



- 1. USB Connector
- 2. Power LED
- 3. USB 3.0 Ports



- 4. RJ-45 Ethernet Port
- 5. LED Indicators
- 6. Power Port*
- * Power adapter is not included.

Key Features

www.level1.com Page 1 of 4

- Παρέχει μία σύνδεση Internet μέσω μίας μονής θύρας USB
- Ταχύτητα μετάδοσης και λήψης καλωδίου 10/100/1000Mbps
- Ενσωματωμένος διανομέας 3 θυρών USB 3.0 Super Speed
- Συμβατό με τα πρότυπα USB 3.0 / 2.0
- Πλαίσια Jumbo 4Κ για αύξηση ταχύτητας μεταφοράς δεδομένων
- Ενσωματωμένη δυνατότητα Wake-on-LAN για απομακρυσμένη εκκίνηση/τερματισμό υπολογιστών
- Διαχείριση και ανάπτυξη σε λειτουργία δικτύου ΙΡν6
- Δεν απαιτείται πρόσθετη παροχή ρεύματος
- Ο έλεγχος ροής ΙΕΕΕ 802.3x παρέχει προστασία ενάντια στην απώλεια πακέτων για αξιόπιστη μετάδοση δεδομένων
- Ελαχιστοποίηση αποτυπώματος άνθρακα με προηγμένη τεχνολογία ενεργειακής απόδοσης (ΙΕΕΕ 802.3az)
- Υποστηρίζει Windows XP / Vista / 7 / 8 ; Mac OS X 10. 6 / 7 / 8

Works Well With



FSW-0508TX

5-Port Fast Ethernet Switch



WAP-6012

300Mbps Wireless Gigabit PoE Access Point



WAP-6013

300Mbps Wireless Access Point (AP, Client, WDS, Repeater)

Specifications

System Specifications

Connectors and Cabling:

USB 3.0 (2.0 Compliant)

1 x 10/100/1000Base-T Auto-MDIX RJ-45 Port

3 x USB3.0/USB2.0 Type A female downstream port

Indicator:

Green: LAN Connected

Amber: LED on when connected to a 1000Mbps; Off when connected to a 100/10Mbps network

Power

Power Consumption (W): Operating Mode: 2.5W

Suspend Mode: 0.4W

Power Input: USB Bus -powered DC5V/900mA

Standards & Protocols:

General: IEEE 802.3: 10Base-T (Ethernet)
IEEE 802.3u: 100Base-TX (Fast Ethernet)
IEEE 802.3ab: 1000Base-T (Gigabit Ethernet)
IEEE 802.3x Flow Control (full-duplex flow control)

IEEE 802.3az Energy Efficient Ethernet

www.level1.com Page 2 of 4

Physical Specifications

Dimensions (W x D x H mm):

79 x 44 x 20 mm (with cable)

Weight (g):

68g

Performance

Data Transfer Rate:

10/100/1000Mbps

Jumbo Frame (K):

4K

Features

General:

IPv6: IPv4/IPv6 network operation

Management:

Power: Wake-on-LAN

Environment

Power Saving:

Stand by mode

Temperature (°C):

Operating: 10 ~ 40°C Storage: 10 ~ 80°C

Humidity (Non-condensing):

Storage: < 85% Operating: < 85%

Others

Approval and Compliance:

CE, FCC

Operation Systems:

Windows XP / Vista / 7 / 8; Mac OS X 10.6 / 7 / 8

www.level1.com Page 3 of 4

Diagram



Order Information

USB-0502

No responsibility for any errors or omissions. All mentioned brand names are registered trademarks and property of their owners. Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.

www.level1.com Page 4 of 4