



WRE-6001C Έκδοση υλικού (h/w): 1

Wireless Range Extender, 300Mbps 802.11b/g/n, EU Plug

The LevelOne WRE-6001C is a versatile, easily deployed WiFi range extender that offers excellent speed and security for expanding a home or office network. Designed for mounting to a wall, the WRE-6001C can be deployed in a convenient area, maintaining a low profile while extending the range of the WLAN. Clever engineering allows for a simple push-button setup, and with three levels of security (WPA-PSK, WPA2-PSK and WEP), the device offers uncompromising security and quality in a simple set-and-forget package.



Βασικά χαρακτηριστικά

- Provides stable signals and extends coverage
- Κοινή χρήση του ασύρματου δικτύου σας έως και 300Mbps
- Συμβατό με τα πρότυπα ασύρματης δικτύωσης IEEE 802.11b/g/n
- Απλή ασύρματη συνδεσιμότητα και ασφάλεια με κουμπί WPS
- Ασύρματη ασφάλεια με κρυπτογράφηση WPA/WPA2-PSK και 64/128-bit WEP

Προδιαγραφές

System Specifications

Standards & Protocols:

IEEE 802.3 10-BASE-T, Ethernet
 IEEE 802.3u 100-BASE-TX, Fast Ethernet
 IEEE 802.11e Wi-Fi Multimedia (WMM)
 IEEE 802.11i Wi-Fi Protected Access (WPA2)
 IEEE 802.11b, IEEE 802.11g, IEEE 802.11n Wireless Networking

**Connectors and Cabling:**

1x 10/100Mbps Base-TX

Button:

WPS Button

Reset Button

Indicator:

Power, Wifi signal, WPS, LAN,

Power:

Power plug (110~ 220V)

Wireless

Operating Mode:

Repeater Mode

Encryption:

WEP 64/128-bit Web share key encryption

WPA, WPA2-PSK TKIP/AES encryption

Receive Sensitivity(dBm):

802.11n (20MHZ): Range (-72 ~ -87) dBm

802.11n (40MHZ): Range (-68 ~ -87) dBm

802.11g: Range (-72 ~ -91) dBm Error Rate = 10% at room temperature
802.11b: Range (-89 ~ -91) dBm Error Rate = 8% at room temperature

Channel:

Ch.1 ~ 11 USA

Ch.1 ~ 13 EU

EIRP(dBm):

(Controllable for different country regulations)

802.11n: up to 14dBm ± 1dBm

802.11g: up to 15dBm ± 1dBm

802.11b: up to 18dBm ± 1dBm"

Antenna:

2 PCB antenna 3dbi

Frequency Band (GHz):

2.4 ~ 2.4835 GHz

Data Transfer Rate:

802.11n: 300 ~ 78 Mbps

802.11g: 54 ~ 6 Mbps

802.11b: 11 ~ 1 Mbps"

Features

General:

Auto Channel Selection

Security:

Wi-Fi Protect Setup (WPS) Push Button

SSID Broadcast On/Off

Wireless Isolation

Management:

Web-Based GUI Configuration

QoS:

802.11e WMM Supported

Ease of Use:

Web-based GUI with Quick Installation Wizard
Web-based (HTTP) firmware upgrade

Performance

Number of Clients:
20

Environment

Temperature (°C):

Operating: 0°C ~ 40°C,
Storage: -10°C ~ 70°C

Humidity (Non-condensing):

Storage: 0 ~ 95%
Operating: 10 ~ 90%

Others

Approval and Compliance:
CE, FCC

Διάγραμμα



Order Information

WRE-6001C

Περιεχόμενα συσκευασίας

WRE-6001C
RJ45 Ethernet Cable
Quick Installation Guide

No liability or responsibility for any errors or omissions in the content.
Specifications are subject to change without notice.
All mentioned brand names are registered trademarks and property of their owners.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.